



Nylon hammer plug PZ Ø 5 x 40 mm (x 100)



Characteristics

Drilling Ø (mm) : 5
Plug length (mm) : 35
Minimum drilling depth (mm) : 45
Thickness to be fixed (mm) : 11
Recommended charges for concrete C16/20 to C50/60 (kg) : 180
Recommended charges solid brick (kg) : 160
Tear-out resistance * C20/C25 concrete (daN*) : 60
Tear-out resistance brick (daN*) : 50
Concrete shearing resistance (daN*) : 50
Quantity per box : 100

Materials

- ☑ Concrete
- ☑ Solid brick
- ☑ Stone

Benefits

- Simple and quick installation with a hammer!

GENERAL INFORMATION

Technical details

Polyamide 6.
 Reinforced flat collar.
 Supplied with white galvanised steel screws.

Application(s)

To attach chutes, raceways, corners, etc.

Instructions

1. Drill the support to the Ø indicated.
2. Insert the wall plug.
3. Insert the screw using a hammer.
4. The wall plug is expanded and in position.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 12
Length (cm) : 9
Depth (cm) : 6
Net weight (kg) : 0,27
Gross weight (kg) : 0,29



Outer package 1



Carton box

Height (cm) : 12,5
Length (cm) : 37
Depth (cm) : 37
Gross weight (kg) : 7,21

x 24.00



Outer package 2



Pallet

Height (cm) : 128
Length (cm) : 120
Depth (cm) : 80
Gross weight (kg) : 389,34

x 1248.00

